

PERKINS 11040-441A - 100 HP - Stage IIIA/ Her 3		-	-	_	_	-	_	_
PERKINS 1104D-E44TA - 130 HP - Stage IIIA/Tier 3		-	-	-	-	-		
DIMENSIONS								
Overall width	mm	2100	2100	2100	2300	2300	2300	2300
Overall length to forks face	mm	4507	4507	5056	4669	4869	4869	4975
Overall height	mm	Low Cab: 2100 (20") / 2184 (24") High Cab: 2250 (20") / 2334 (24")	Low Cab: 2100 (20") / 2184 (24") High Cab: 2250 (20") / 2334 (24")	Low Cab: 2100 (20") / 2184 (24") High Cab: 2250 (20") / 2334( 24")	2290 (20") / 2374 (24")	2290 (20") / 2374 (24")	2290 (20") / 2374 (24")	2374 (24")
HYDRAULIC SYSTEM								
Pump type		Gear pump with LS valve	Gear pump with LS valve	Gear pump with LS valve	Load sensing pump	Gear pump with LS valve	Load sensing pump	Load sensing pump
Distributor		Electro-proportional with flow sharing						
Pump capacity (with 75 HP engine when available)	l/min	100 (80)	100 (80)	100 (80)	190	100	190	190
Working pressure	bar	250	250	250	255	250	255	255

## A NEW ERA

## A telescopic loader designed around you

The Bobcat TL range of telescopic loaders is designed to excel in the most demanding agricultural applications. These versatile machines incorporate all the benefits of our long experience and dedication to constant improvement. They combine tried and tested principles with innovative design, state-of-the-art technologies and a commitment to meeting the ever-growing demands of your working day. The Bobcat TL range delivers all the power needed in a compact, strong and agile machine, developed with the operator right at the centre of the design.







## **AGRICULTURAL TELESCOPIC LOADERS**









One Tough Animal.











